

For evacuation of air

B078R06

With vacuum gauge (-1 to 0 bar)

Portable vacuum pump unit (10 m³/h, < 1 mbar)

Operating voltage: 220 - 240 V / 50 - 60 Hz alternating current

B078R06S15

Portable vacuum pump unit (10 m³/h, < 1 mbar)

Operating voltage: 110 - 127 V / 50 - 60 Hz alternating current



B078R16

With digital vacuum indication (0 to 400 mbar)

Portable vacuum pump unit (10 m³/h, < 1 mbar)

Operating voltage: 220 - 240 V / 50 - 60 Hz alternating current

B078R16S15

Portable vacuum pump unit (10 m³/h, < 1 mbar)

Operating voltage: 110 - 127 V / 50 - 60 Hz alternating current



Technical data B078R06:

| |
|--|
| Dimensions: L 420 mm, W 200 mm, H 320 mm |
| Weight: 20 kg |

Technical data B078R16:

| |
|--|
| Dimensions: L 470 mm, W 200 mm, H 345 mm |
| Weight: 21 kg |

Standard equipment:

| |
|---|
| 10 m ³ /h vacuum pump with exhaust filter, final vacuum < 1 mbar |
| Ball valve DN8 |
| 3 m long rubber hose DN8 with DILO coupling tongue part DN8 |
| 2.5 m long electrical connecting cable |
| 2 operating manuals in German, English or French |

Optional accessories at an extra charge:

| | |
|---|-------------|
| SF ₆ gas refilling device | 3-393-R001 |
| Coupling adapters DN8 for evacuation of hoses | 6-1059-R012 |
| Additional operating manual on CD-ROM | 6-0004-R213 |
| Aluminium transport case | 3-781-R011 |

Spare parts kit:

| | |
|-------------------------------------|-------------|
| Maintenance package for vacuum pump | 6-1048-R101 |
|-------------------------------------|-------------|

Packing:

| | |
|---------------------|--------------|
| Packing for B078R.. | 3-748-R003-C |
|---------------------|--------------|